N20/30 FF030

> RF130 BLDC 1632

FF130

FF180

RF500 RF300

RF310

094 BLDC

370 2418

2430 385

2838

395

30-C 32-C

40-C 32ZY13

32ZY25

> 555 BLDC 3640

> > 775

38S BLDC 38S 45S

BLDC 45S 50S BLDC 50S

60S BLDC 60S 80S

稳压器

同步 电机 永磁 直流电机 交流


可逆电机


FHB60KTYZ AC Synchronous Gear MOTOR

Material	Metal			
Output Bearing	Oil Bearing			
Radial Force	≤ 8 kgf			
Axial Force	≤ 3 kgf			
Spindle Pressure	≤ 15 kgf			
Radial Clearance	≤ 0.1 mm			
Axial Clearance	≤ 0.3 mm			



Dimension(mm):







Technical Data:

Environment Temp.	-15 ~ +45° C
Humidity	15% ~ 90%RH
Working Volt.	85% ~ 110% of Nominal Volt.
Frequency	Nominal Frequency±3%
Installation	Shaft keep horizontally or upward

Technical Data:

Nominal Volt. (V)	220									
Nominal Frequency(HZ)	50-60									
Working Duty (S)	S1									
Capicitor applicable (µF)	0.68									
Input Power (W)	< 22									
Input Current (mA)	< 100									
Output speed (r/min)	3	5	7	10	15	20	30	40		
Output torque (Kg/cm)	130	100	72	50	30	25	17	13		
Direction	CW/CCW									
Insulation Class	E									
Dielectric Strength	1800V/S									
Temp.rising (K)	< 65									
Noise (dB)	小于 45									

Note: If you need different power, or special design on shaft, please inquiry us.